

KE-96J

Technical Data Sheet

MICROBIOCIDE

Microbiocide 96J is a 8.75% blend of Disodium cyanodithiomidocarbonate and Potassium N-methyldithiocarbamate. Microbiocide **96J** is used to control algae and bacteria in recirculating commercial and industrial water cooling towers.

PRODUCT DESCRIPTION

Physical State	-	Liquid
Color	-	Red-orange
Odor	-	Pungent sulfite
Specific Gravity	-	1.07
pH	-	11.5

INDUSTRIAL/COMMERCIAL RECIRCULATING COOLING WATER TOWERS

Microbiocide **96J** is a product formulated to provide control of the growth of algae and bacteria in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. The frequency of subsequent additions depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of the water cooling towers.

DOSAGE

The frequency of feeding and duration of the treatment will depend upon the severity of the problem. Badly fouled systems must be cleaned before treatment is begun. Follow dosage directions on product label for specific application. Consult *Kinzua Inc.* technical staff for continuous feed equipment.

HANDLING

Microbiocide **96J** is an EPA registered product. It must be used and disposed of according to label instructions. Do not contaminate water, food, or feed by storage or disposal. Microbiocide **96J** is corrosive causing eye and skin damage. Do not take internally. Avoid contact with skin and eyes. Should contact occur, flush immediately with water. If any discomfort persists, seek medical attention. Read relevant Material Safety Data Sheet and product label before handling this product.

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com