


KE-44

PERMANENT COLD PATCH

TECHNICAL DATA



PERMANENT COLD PATCH.... is a ready-to-use, pre-mixed asphalt patching material made from a combination of selected aggregate, asphalt with chemical solvents and additives. The tenacious binding adhesive creates durable, permanent repairs and restores dangerous ruts and potholes to a safe, level surface for traffic, in a matter of minutes. It is recommended for use in patching pavement on highway roads, streets, railway crossings and bridge decks. Can be applied to either wet or dry surfaces in both hot or sub-freezing temperatures.

FEATURES/BENEFITS.....When applied to wet and frozen potholes it will compact with the back of a shovel and may then be opened to traffic immediately. The combination of materials resists rutting while providing excellent bearing strength. Where other cold mix material may ravel and lift out because the base asphalt material will not adhere to the aggregate, or because the cut-back agents enlarge the original hole, PERMANENT COLD PATCH will continue to perform. Can be used in wet or dry conditions and in temperatures from minus 15° through 100° F. PERMANENT COLD PATCH will adhere to steel, concrete, and asphalt surfaces. It is ideal for utility cuts, railway crossings and of course potholes and broken edges on parking areas, streets and highways.

DIRECTIONS...For potholes, remove all loose debris and shovel in enough PERMANENT COLD PATCH to slightly crown the surface. Tamp with the back of a shovel or wheel roll with any vehicle. For large or deeper repairs, remove all loose debris and apply in 2 to 3 inch layers, compacting each layer. Where the subsurface has been disturbed, as in a utility cut, it is necessary to compact the backfill in the cut as for any patching operation. Should adequate compaction not be achieved, and additional settlement occur, further applications of PERMANENT COLD PATCH or an overlay of conventional asphalt can be applied later to compensate.

STOCKPILE AND STORAGE.....Outdoors in an uncovered stockpile for two years, and indefinitely in containers, without losing its adhesive effectiveness.

COVERAGE.....5 sq. ft. per gal. at 3/8 of an inch thick. **COLOR....**Black

DRYING TIME.....Immediate. Once PERMANENT COLD PATCH has been applied, traffic can be immediately resumed since no setting time is required to produce a permanent patch.

Kinzua Environmental, Inc.
1176 E. 38th St.
Cleveland, Ohio 44114
800-233-5079
www.kinzuachem.com
