

KINZUA

KE-137B

EPOXY CONCRETE SEALER

Epoxy Concrete Sealer combines the tough durability of epoxy ester resin with the convenience and simplicity of one component application. Dries to a transparent protective seal that prevents chemical penetration and dusting of concrete floors.

RECOMMENDED USES

This product is as an economical concrete floor sealer and finish for industrial use in manufacturing operations, warehousing facilities, indoor walkways, anywhere a tough, durable, lustrous finish is desired.

U.S.D.A. AUTHORIZED FOR USE IN FEDERALLY INSPECTED MEAT AND POULTRY PLANTS

MFMA CERTIFIED GYM FLOOR FINISH.

PRODUCT CHARACTERISTICS

- Provides a tough transparent seal that is resistant to dust, abrasion, impact, alkali, oil, grease, ink, fruit juice, cleaners, alcohol and moisture.
- Stops concrete from dusting and deteriorating.
- Simple application - comes ready to use, no messing mixing or measuring.
- Excellent leveling characteristics prevent formation of bubbles and lap marks, for a professional finish every time.
- Durable - formulated to stand up to everyday wear and abuse.
- Economical - costs up to 65% less than water-base epoxies.
- Beautifies - dries to an excellent gloss that will not cloud, nor yellow with age.

COVERAGE

First Coat: 300 - 400 square feet per gallon
Additional Coats: 400 - 500 square feet per gallon

DRY TIME

To Touch 1-3 hours
Hard 5-8 hours
Between Coats 10 - 12 hours

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com