

KINZUA

KE-178B & KE-178B1

EPOXY ENAMEL

KE-178B / 178B1 combines the tough durability of epoxy ester resin with china wood oil and simplicity of one component application. Dries to a colorful protective seal that prevents chemical penetration and dusting of concrete floors.

KE-178B = Lt. grey / red / dk.grey / black KE-178B1 = white / green / yellow

RECOMMENDED USES

This product is as an economical concrete floor enamel paint for industrial use in manufacturing operations, warehousing facilities, indoor walkways, anywhere a tough, durable, lustrous finish is desired.

U.S.D.A. AUTHORIZED FOR USE IN FEDERALLY INSPECTED MEAT AND POULTRY PLANTS

Do not use on newly laid concrete floor.
Concrete must be completely cured.

PRODUCT CHARACTERISTICS

- Provides a tough enamel seal that is resistant to dust, abrasion, impact, alkali, oil, grease, ink, fruit juice, cleaners, alcohol and moisture.
- Stops concrete from dusting and deteriorating.
- Simple application - comes ready to use, no messing mixing or measuring.
- Excellent leveling characteristics prevent formation of bubbles and lap marks, for a professional finish every time.
- Durable - formulated to stand up to everyday wear and abuse.

COVERAGE

First Coat: 300 - 400 square feet per gallon
Additional Coats: 400 - 500 square feet per gallon

DRY TIME

To Touch 1-3 hours
Hard 5-8 hours
Between Coats 10 - 12 hours

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com