

# KE-178D

## HEAVY DUTY NON-SKID SAFETY COATING WITH EPOXY RESIN

Single part enamel, with integrated silica type grit, provides a durable coarse non-slip surface. Exceptional gasoline and oil resistance. Also resists hydraulic oils, grease, alcohol, etc.

### RECOMMENDED USES

This product is designed to provide sure, safe footing on wet or sloped areas in manufacturing operations, warehousing facilities, indoor walkways, ramps, loading docks, anywhere a tough non-slip surface is required. Concrete must be at least 90 days old before using this product.

### PRODUCT CHARACTERISTICS

- Prevents hazardous working conditions.
- Simple application - comes ready to use, no messy measuring or mixing
- Durable - formulated with epoxy resin to stand up to wear and abuse.
- Economical - just apply with roller.
- Versatile - use on concrete, wood or stone floors.
- Beautifies - available in gray, green, red, black or beige.
- Low VOC - meets California, New York and all other clean air regulations.

### TECHNICAL DATA

Coverage . . . . .	150 square feet per gallon
Dry Time . . . . .	To Touch - 3 hours
. . . . .	Hard 6 - 8 Hours
. . . . .	Open to Traffic 12 - 24 hours
. . . . .	Between Coats 5 - 6 hours
Colors . . . . .	Gray, Green, Red, Yellow,
. . . . .	Black, Beige

Kinzua Environmental, Inc.  
Cleveland, Oh. 44114  
800-233-5079  
[www.kinzuachem.com](http://www.kinzuachem.com)