

Make **KE-400** Your Quick, Easy Epoxy Repair Mix

Repair cracked or spalled concrete with **KE-400** from **Kinzua**. This innovative 3-part epoxy kit includes resin, hardener and aggregate for fast, easy bonding to 1/64".

KE-400 sets up in only 1 hour, is ready for foot traffic in 8 hours and can handle tow motor traffic in 12 hours. It's available in **FIVE GALLON** kits for your convenience.

Follow These Steps for Simple Concrete Repair

1
Cracked, spalled or worn concrete is easy to repair and maintain with **KE-400**.



2
Start the repair process by cleaning the area.



3
A wire brush or a scarifier, as shown here, makes cleaning easy.



4
The area is now clean.



5
The **KE-400** system includes resin, hardener and aggregate.



6
To prepare **KE-400**, mix the 3 parts together - resin and hardener first, then add aggregate.



7
Fill the cracked area. Pot life is 1 hour.



8
Spread and smooth out **KE-400**.



9
The patched area looks like new. **KE-400** is available in 5 colors for easy matching. **Tan** **Brick Red** **Light Grey** **Dark Grey** **Black**
Other colors available



10
Use a rag for quick, easy cleanup.



Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com

KE-400 3-PART EPOXY PATCHING SYSTEM FOR

Concrete - Steel - Wood

SMOOTH-PERMANENT-LONG-WEARING

400 Epoxy Patch has a 100% Epoxy resin Base, a catalyst hardener, and a special aggregate to make it the most durable patching system available for concrete, steel or wood. Extra long-wearing and resilient, **400 Epoxy Patch** withstands heavy trucking, absorbs vibration and shock without cracking - actually becomes stronger with use.

400 Epoxy Patch makes quick and easy work out of mending jobs, indoors or out. Now you can repair floors with a minimum of down time.

400 Epoxy Patch can be used to renew and mend pitted floors, seal cracks, bridge expansion joints, fill chuck holes where a non-shrink, non-corrosible and chemical resistant filler is required. Excellent for anchoring machinery.

400 Epoxy Patch has a wide range of applications and can be done by inexperienced maintenance men on: Parking Areas, Docks, Walks, Driveways, Floors, any surface of Concrete, Steel or Wood in: Garages and Service Stations, Warehouses, Refineries, Chemical Plants, Laundries, Textile Mills, Machine Shops, Printing Plants, Aircraft Hangars, etc.

400 Epoxy Patch dries in 8 to 10 hours for light traffic, and 12 hours for Tow Motor traffic. .

400 Epoxy Patch has excellent coverage. At a solid 1/4 inch thickness it will completely cover 22 to 24 square feet - it is hard to imagine the number of patches it can make!

FOR A CLEAN, SOUND SURFACE:

Before patching we recommend these procedures:

1. A thorough stripping and degreasing with **KE-22 Cleaner Degreaser** for heavy incrustations of oil, grease, etc.
2. **KE-147 Concrete Etch** cleans surfaces and etches to provide a "tooth" or roughness for better adhesion.

NOTE: All 3 parts of KE-400 are packaged in a 5 gallon pail. The base in a 1/2 gallon can, catalyst in a quart can, the balance is aggregate.

Kinzua Environmental, Inc., Cleveland, Oh. 44114, 800-233-5079
www.kinzuachem.com