

KE-67 SERIES

DOUBLE SOLIDS

FLOOR FINISH



DESCRIPTION

The right product for beautiful, safe floors requiring minimum maintenance. This modern blend of clear acrylic polymers is easy to apply, dries to a high gloss without polishing, resists black marks and scuffing, resists tracked in water, is not harmed by surface cleaning with detergents, but can be removed easily when desired.

USES

Vinyl, VAT, VCT, rubber, linoleum, marble, terrazzo, concrete, brick, flagstone, epoxy and other resilient and non-resilient floors.

HOW TO USE

PREPARATION: May be applied over other hard, non-wax floor finishes if they are clean and in good condition, but for best results we suggest at least top stripping with our companion stripper. Then rinse thoroughly and allow floor to dry.

APPLICATION: Apply in thin coats. Lay finish in "figure 8" strokes, slightly overlapping each pass. Avoid contact with finish as it dries. Allow each coat to dry 20-30 minutes before applying a next coat or walking on floor.

NOTE: Humid conditions may require longer drying times between coats.

MAINTENANCE: Dust mopping and damp mopping will keep floors bright and shiny. When under heavy traffic, if the floor becomes dull, this finish is an excellent base for spray buffing.

Recommended for vinyl, vct, asphalt tile, rubber, linoleum, marble, terrazzo, concrete, finished wood.

BENEFITS

MORE DURABLE: Other finishes may not literally wear through, but they pick up dirt and black marks, become badly scuffed and discolor necessitating stripping and recoating. **KE-67** stays clean and clear.

HIGH GLOSS: Dries to a high gloss without polishing and is an excellent base for spray buffing to a brilliant, mirror-like finish

WATER RESISTANT: Completely impervious to spills and to water tracked on floor during bad weather.

DETERGENT RESISTANT: Floors maintained with **KE-67 Finish** can be mopped or even scrubbed with mild detergent solutions without removing the finish or harming its gloss.

EASILY REMOVED: In spite of its resistance to water and detergents, **KE-67 Finish** can be easily removed with its companion stripper when desired.

SLIP RESISTANCE:

**Meets ASTM Standards
with JAMES slip test
machine**

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com