

KE-81

Data Sheet

COLD PARTS DEGREASER

EMULSIFIER SOLVENT DEGREASER

**SUPER CONCENTRATED
EMULSIFIER AND
DEGREASER**

Solvent degreaser

Motor and Parts Cleaner

**Engine blocks, transmissions, locomotives, truck bodies,
small parts, tools**

**Removes cosmoline and undercoating overspray from
automotive surfaces**

Safe on painted surfaces

**Surface flushes clean
with water using hose or
pressure washer**

**NON-CAUSTIC
NON-ACID
NEUTRAL pH**

**May be used on concrete floors,
masonry walls, metal parts**

**Formulated with a wetting agent
to improve solvent penetration into
soil and an emulsifier to flush
cleaned surface with water**

**EASY TO APPLY
WITH MOP, SPRAY,
SOAK TANK OR
OTHER SUITABLE
METHOD**

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com

DESCRIPTION

KE-81

A low toxicity solvent type cleaner for oily and greasy soils from solvent resistant surfaces. Formulated with a wetting agent to improve solvent penetration into soil and an emulsifier to flush cleaned surface with water. The diluted product has a neutral pH which is easy on hands and safe on most painted surfaces.

APPLICATION

Solvent dilutes grease or oil holding soil and emulsifier renders the system water-soluble thus releasing the solvent, oil or grease, and soil from the surface. Removes grease and oil from engine blocks, transmissions, truck bodies, small parts, tools and concrete floors. Removes cosmoline and undercoat overspray from automotive surfaces.

DIRECTIONS FOR USE

CONCENTRATED CLEANER AND DEGREASER may be sprayed or wiped onto surface or used in a dip tank. Allow the product to loosen the built up dirt. Agitation or scrubbing will increase effectiveness and speed cleaning time. A simple hosing down with water will emulsify the grease, dirt, and solvent and wash them away. FOR EXTREMELY HEAVY APPLICATIONS: Use full strength or dilute with 2 or 3 parts kerosene or other solvents. FOR NORMAL APPLICATIONS: Dilute with 4 to 5 parts kerosene or other solvents. TO REDUCE FIRE HAZARD: This product may be diluted with 1 to 3 parts water. This dilution should be agitated with an open airline to prevent separation. FOR RUST PREVENTION: Spray or wipe a light film of full strength product onto previously cleaned surfaces.

SPECIFICATIONS

Appearance: Clear liquid
Fragrance: Characteristic
pH: 6.00
Flash point: 143°F. Combustible

PRECAUTIONS

Keep out of reach of children. Combustible. May cause eye or skin irritation. Do not get in eyes, on skin or on clothing. Do not take internally. Avoid breathing vapor. Use protective eye and skin gear. Keep away from heat and open flame. Keep container closed. Use only with adequate ventilation. Do not reuse container. Rinse empty container with water and discard. This product is intended for industrial and commercial use and storage by trained service persons only. Manufacturer will not be responsible for any injury, loss, or damage, if product is used in any manner not in compliance with label directions or if precautions are not observed.

FIRST AID

EYES: Flush with large amounts of water for at least 15 minutes; contact physician. IF SWALLOWED: Do not induce vomiting or give anything by mouth to an unconscious person. Seek medical attention. EXTERNAL: Flush with water. Remove and wash contaminated clothing before reuse.