

## Product Specifications

**Appearance:**  
Light Foam

**Odor:**  
Solvent

**pH:**  
NA

**Storage:**  
Below 120°F (49°C)

**Boiling Point:**  
<0 to 342°F

**Vapor Density:**  
Heavier than air

**Evaporation Rate:**  
Slower than Ether

**Specific Gravity:  
(Water = 1)**  
0.80 ± 0.05

**Solubility in Water:**  
Nil

Kinzua Environmental, Inc.  
Cleveland, Ohio 44114  
800-233-5079  
[www.kinzuachem.com](http://www.kinzuachem.com)

## Product Information Sheet

# KE-240E

## Foaming Rust Penetrant with Graphite

### DESCRIPTION

A superior blend of lubricants, solvents and moisture displacing oil. Foaming action provides extended penetration and moisture displacement. The light foam of this product allows for "creeping" in any direction.

### FEATURES AND BENEFITS

Outstanding penetrant that loosens the toughest rust. Contains oily lubricants to assist in removal of nuts back off threads. Penetrants creep between mating parts for faster, safer loosening. Foaming action minimizes run off and keeps more product working on the rusted part.

### APPLICATIONS AND USES

Penetrates, busts rust, cleans, displaces moisture, protects, and provides long term lubricity on any surface.

### DIRECTIONS FOR USE

Shake well before using. Spray **KE-240E** on all corroded, rusted or frozen parts. Let stand for several minutes to allow thorough penetration. If necessary, tap lightly to speed and insure penetration. In extreme cases a second application may be necessary.

HMIS	
HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	B

