

KE-270

Paint Remover

**Gel Base – Will Not Run
Removes Paint, Decals,
Gaskets and Varnish**

CAUTION:
HARMFUL IF SWALLOWED
VAPOR HARMFUL
CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
See Additional Cautions On Back Panel

NET WT. 13 OZ. (369 g)

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com

KE-270 PAINT REMOVER

Gel formulation paint remover quickly removes paint, epoxy, lacquer, decals, gaskets, shellac, enamel, varnish, labels, gasket cement, glue, carbon deposits, silicone and simulated wood paneling. Product will not run. This formula has been authorized by the USDA for use in federally inspected meat and poultry plants.

For use by auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. For use on metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.

DIRECTIONS

Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

CAUTION: Contains methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to health depends on level and duration of exposure.

CAUTION: Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120° F may cause bursting. Use this product outdoors, if possible. If you must use it indoors, open all windows and doors or use other means to ensure fresh air movement during use. Avoid prolonged breathing of vapor or contact with skin or eyes. In case of contact with eyes, flush thoroughly with water. If swallowed, induce vomiting. Call a physician immediately.

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

INGREDIENTS: Methylene Chloride (CAS# 75-09-2), Propane-Isobutane (CAS# 68476-85-7), Methanol (CAS# 67-56-1), Methylcellulose (CAS# 9004-65-3), Petroleum Wax (CAS# 64742-43-4)

HEALTH	2
FLAMMABILITY	1
REACTIVITY	2
PERSONAL	2



**TECHNICAL
DATA**

KE-270

PAINT REMOVER

KE-270 is a USDA authorized gel base paint remover. Penetrates deep to remove paint, decals, gaskets, glue and labels from all surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces.

AREAS OF USE

AUTO DEALERS
PAINT SHOPS
FACTORIES
MOTELS
HOTELS
SCHOOLS
HOSPITALS
HOMES
RESTAURANTS

APPLICATIONS

PAINT
DECALS
EPOXY
LACQUER
GASKETS
GLUE
CARBON DEPOSITS
SILICONE
SIMULATED WOOD PANELING

TECHNICAL DATA

FORM: Solvent Base Aerosol
ODOR: Strong Chlorinated Solvent
COLOR: Clear
DETERGENCY: Excellent
TOXICITY: 500 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 year +
COLD STABILITY: 0° F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY: 1.2
% VOLATILE BY VOLUME: 27%
pH: N/A
PROPELLENT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079
www.kinzuachem.com