

# Product Data Sheet

## **KE-3035**

### **CUTTING & TAPPING COMPOUND**

#### **DESCRIPTION**

A foaming oil that clings to all cutting tools, preventing waste and over-spraying. Reduces friction in the process of threading, reaming, tapping and drilling process. Contains ingredients to prevent rancidity, and foam control for high agitation procedures.

#### **FEATURES AND BENEFITS**

Thick foam that clings to vertical surfaces. Combines synthetic and natural lubricants for maximum high pressure lubrication which will increase the cutting rate without overheating. High performance cooling action allows for higher cutting speeds for increased productivity.

#### **APPLICATIONS AND USES**

Works in Boring, cutting, tapping, grinding, machining, punching, sawing and more. Blended for high load tolerance and to leave a temporary, rust inhibitive coating. Use in industrial plants, machine shops, automotive shops, metalworking shops, oil rigs, and industrial manufacturers.

#### **DIRECTIONS FOR USE**

Shake well before using. Spray a moderate amount of foam on the cutting tool. Re-spray often to keep tools cooled and lubricated. Reapply as necessary.

#### **SIZE / AVAILABILITY**

16-oz. Aerosol  
Net Weight 14 oz.  
12 per case

HMIS	
HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	0



**Kinzua Environmental, Inc.**  
**Cleveland, Oh. 44114**  
**800-233-5079 / [www.kinzuachem.com](http://www.kinzuachem.com)**