

KE-3036 AIR TOOL OIL



DESCRIPTION

AN OIL THAT CLEANS, LUBRICATES AND RECONDITIONS AIR-OPERATED POWER TOOLS.

DIRECTIONS FOR USE

SPRAY INTO ALL OPENINGS INCLUDING AIR INLET CONNECTION. ALLOW OIL TO PENETRATE FOR SEVERAL SECONDS. RUN AIR TOOL AT MAXIMUM RPM FOR 30 SECONDS. REPEAT PROCEDURE FOR SEVERE CONDITIONS.

APPLICATIONS AND USES

CLEANING AND LUBRICATING AIR OPERATED TOOLS; JACKHAMMERS, DRILLS, SAWS, IMPACT WRENCHES, SANDERS, POLISHERS, GRINDERS AND OTHER TYPES OF AIR-OPERATED MOTORS. EXCELLENT APPLICATION FOR USE PRIOR TO LONG-TERM STORAGE.

FEATURES

- ELIMINATES CALCIUM BUILD-UP FROM MOISTURE IN AIR LINES.
- DISSOLVES SLUDGE, DIRT, AND DUST ACCUMULATION.
- RESTORES AIR TOOLS TO PEAK POWER AND RPMS.

BENEFITS

- ENABLES AIR PRESSURE TO PENETRATE MORE FREELY GIVING MORE POWER TO TOOL.
- ENABLES MOTOR PARTS TO MOVE MORE FREELY.
- ENABLES TOOLS TO WORK MORE EFFICIENTLY.

SPECIFICATIONS

APPEARANCE:	RED
ODOR:	SOLVENT
PROPELLANT:	HYDROCARBON
V.O.C.:	59.91%
NFPA 714 - FLAMMABILITY:	4
NFPA 30B - STORAGE:	3

Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079