

KE-3060 RED GREASE



**SPRAYS AS A LIQUID . . .
PENETRATES DEEP
INTO WORKING PARTS . . .
THEN SETS UP
TO A THICK GREASE**

WORKS LIKE A GREASE GUN IN AN AEROSOL CAN

- A LIQUIFIED LITHIUM LUBRICANT THAT PENETRATES INTO MECHANISMS THEN SETS UP TO A RESISTANT GREASE
- LONG LASTING WATER AND DETERGENT RESISTANCE
- PREVENTS RUST
- EXTREME TEMPERATURE (FROM -60°F TO +500°F) and HIGH PRESSURE RESISTANCE
- HELPS FLUSH AWAY OLD CONTAMINATED LUBRICANTS

**Kinzua Environmental, Inc.
Cleveland, Oh. 44114
800-233-5079**

KE-3060 RED SPRAY GREASE

Aerosol
Product
Data
Sheet

Description

A special penetrating formula that sprays as a liquid to flush off old contaminated lubricant, creep deeply into working parts and then set up to a viscous, thick grease. Withstands temperatures up to 500°F. Highly resistant to water, acid and detergent wash-out.

For Use By

FROZEN FOOD PROCESSING • DAIRIES
FREEZE DRYING OPERATIONS
HOT AIR DRYING OPERATIONS
BAKERIES • MARINAS • SHIPPING
AIRCRAFT MAINTENANCE
PACKAGING & MOLDING OPERATIONS
SHIPPING OPERATIONS

For Use On

OVENS • DRYERS • GEARS
VALVES • PUMPS • WINCHES
CONVEYORS • CHAIN DRIVES
FITTINGS • LINKAGES • WIRE ROPE
HOISTS • THREADS • ROLLERS
CAMS • SLIDE BEARINGS • O-RINGS
MANIFOLD HEAT VALVES

Features

**EXTREME TEMPERATURE (-60°F TO +500°F)
and HIGH PRESSURE RESISTANCE
HOLDS UP UNDER HIGH SHOCK LOADS
REDUCES FREQUENCY OF LUBRICATION
PENETRATES DEEPLY INTO DIFFICULT TO LUBRICATE PLACES
RESISTS ACIDS, OXIDATION, DIRT AND SALT SPRAY**

Specifications

Appearance and Odor	Red Viscous Liquid, Solvent Odor
Flash Point of Concentrate	51°F (T.O.C.)
Aerosol Flammability	Extremely Flammable Spray
Specific Gravity of Concentrate	1.100
Propellant	Liquified Petroleum Gas
Spray Pattern	Coarse Circular
NFPA Fire Rating	Level 3 Aerosol