

# KE-7070 THRU KE-7078

## SLIP RESISTANT EPOXY COATING

*Helps Meet OSHA Requirements!*



- PROVIDES ONE PART ROUGH GRIP SURFACE

- EASY TO APPLY
- SETS UP FAST
- CONVENIENT AEROSOL  
NO MIXING - NO MESS

**Adheres to Most Hard Surfaces**

- Most Cost Effective Means of Coating Most Areas
- Contains Synthetic Grit - with No Sharp Edges
- Super Tough - Epoxy Binder
- Lasts From 6 Months to 1 Year (depending on traffic)

**AVAILABLE IN FIVE DISTINCT COLORS:  
CLEAR • GREY • OSHA YELLOW • BLACK • WHITE**

**Kinzua Environmental, Inc.  
Cleveland, Ohio 44114  
800-233-5079**

## SLIP RESISTANT EPOXY COATING

### Description

A slip resistant epoxy coating that cures to a hard, flat, textured finish. Designed for interior and exterior use on concrete, steel, wood, fiberglass, aluminum, tile, etc. Particularly effective anywhere water or other slippery conditions exist. Contains a synthetic grit with no sharp edges. Perfect for use on irregular shapes or anywhere "grit -tape" would not be feasible. Easy to use one part aerosol eliminates mixing, waste, clean-up and application of separate grit.

### For Use by

Apartment Buildings  
Hospitals • Nursing Homes  
Shipping Operations • Industrial Plants  
Municipalities • Schools  
Offices • Warehouses  
Marinas • Machine Shops  
Garages • Construction Companies

### For Use On

Steps • Ladders • Ramps  
Public Restrooms  
Loading Docks • Marine Docks  
Around Industrial Equipment  
Running Boards • Step Pads  
Boats • Pools Decks • Diving Boards

### Features

Easy to Apply  
Sets up quickly  
AVAILABLE IN:

CLEAR, GREY, OSHA YELLOW, BLACK AND WHITE

### Specifications

Appearance and Odor .....	Colored Liquid / Solvent Odor
Flash Point of Concentrate .....	45°F T.O.C.
Flammability .....	Extremely Flammable Spray
Specific Gravity .....	0.800
Propellant .....	Hydrocarbon
Spray Pattern .....	Coarse Circular Fan Spray
NFPA Fire Rating .....	Level 3 Aerosol